

WOLF TRAP

ASSEMBLY

FL3830
FL3831
FL3832



PARTS

- 1X left side bracket
- 1X right side bracket
- 1X cloth sleeve
- 2X 1/2" diameter dowels
- 4X 6-18 x 1-1/4" Phillips flat head sheet metal screws

TOOLS REQUIRED

- #2 Phillips screwdriver

ASSEMBLY

1. Slide the dowels into the casings on the long sides of the cloth sleeve.
2. Line up the side brackets with the large holes facing to the inside.
3. Fit the 1/2" diameter dowels into the holes in the side brackets. From the outside of the bracket, secure the dowels with 6-18 x 1-1/4" Phillips flat head sheet metal screws.
4. Place the assembled Wolf Trap onto the front beam of your loom.

SAFETY CAUTION

For ages 12 and older. Hardware prior to assembly could pose a choking hazard. Allergen notice: A Danish oil finish is used on the wood.



Find out more at schachtspindle.com
Schacht Spindle Company 6101 Ben Place Boulder, CO 80301
303.442.3212

© 2024 Schacht Spindle Company, Inc.

12.24

WOLF TRAP

ASSEMBLY

FL3830
FL3831
FL3832



PARTS

- 1X left side bracket
- 1X right side bracket
- 1X cloth sleeve
- 2X 1/2" diameter dowels
- 4X 6-18 x 1-1/4" Phillips flat head sheet metal screws

TOOLS REQUIRED

- #2 Phillips screwdriver

ASSEMBLY

1. Slide the dowels into the casings on the long sides of the cloth sleeve.
2. Line up the side brackets with the large holes facing to the inside.
3. Fit the 1/2" diameter dowels into the holes in the side brackets. From the outside of the bracket, secure the dowels with 6-18 x 1-1/4" Phillips flat head sheet metal screws.
4. Place the assembled Wolf Trap onto the front beam of your loom.

SAFETY CAUTION

For ages 12 and older. Hardware prior to assembly could pose a choking hazard. Allergen notice: A Danish oil finish is used on the wood.



Find out more at schachtspindle.com
Schacht Spindle Company 6101 Ben Place Boulder, CO 80301
303.442.3212

© 2024 Schacht Spindle Company, Inc.

12.24